



Pneumatic hoses

Recoil hoses PA12

Recoil hoses PA12

This series of nylon recoil hoses is particularly suitable for environments that require robust pneumatic hoses. The hoses are extremely resistant to temperature and pressure, and have an excellent ability to retain their coiled form.

Technical data

Material: Polyamide 12 (PA12)
 Working pressure: Max. 25 bar at 23°C
 Temp. range: -40°C to +100°C
 Surface hardness: Shore D63

Recoil hoses PA12 with relief spring & swivel joint

Connection	Dim.	Work. length	Max. work. pressure	Code no.
1/4" BSPT external thread	ø6 x ø8mm	2,5m	25 bar	1700208-02
1/4" BSPT external thread	ø6 x ø8mm	3,5m	25 bar	1700208-03
1/4" BSPT external thread	ø6 x ø8mm	5m	25 bar	1700208-05
1/4" BSPT external thread	ø6 x ø8mm	7,5m	25 bar	1700208-07
3/8" BSPT external thread	ø7,5x ø10mm	5m	25 bar	1700410-05
3/8" BSPT external thread	ø7,5x ø10mm	7,5m	25 bar	1700410-07
1/2" BSPT external thread	ø9m x 12mm	5m	25 bar	1700512-05
1/2" BSPT external thread	ø9m x 12mm	7,5m	25 bar	1700512-07
1/2" BSPT external thread	ø9m x 12mm	10m	25 bar	1700512-10



1700208-05

Pneumatic hoses

Recoil hoses PUR - "Flex Boy"

Technical data

Material: Polyurethane
 Working pressure: Max. 10 bar at +20°C
 Temp. range: -40°C to +60°C
 Surface hardness: Shore D52

Recoil hoses PUR - "Flex Boy"

Super flexible recoil hoses, capable of bending without being damaged. Maintains persistent flexibility at temperatures as low as -40°C. An oil-resistant hose whose superior qualities are acknowledged in all sectors of industry. We recommend that polyurethane hoses not be used in direct sunlight for long periods of time.

Recoil hoses PUR - Flex BOY with fittings

Connection	Dim.	Work. length	Max. work. pressure	Code no.
1/4" BSPT external thread	ø4 x ø6mm	1m	10 Bar	1710206-01
1/4" BSPT external thread	ø4 x ø6mm	2m	10 Bar	1710206-02
1/4" BSPT external thread	ø4 x ø6mm	4m	10 Bar	1710206-04
1/4" BSPT external thread	ø5 x ø8mm	2m	10 Bar	1710208-02
1/4" BSPT external thread	ø5 x ø8mm	4m	10 Bar	1710208-04
1/4" BSPT external thread	ø5 x ø8mm	6m	10 Bar	1710208-06
1/4" BSPT external thread	ø5 x ø8mm	8m	10 Bar	1710208-08
3/8" BSPT external thread	ø6,5 x ø10mm	2m	10 Bar	1710410-02
3/8" BSPT external thread	ø6,5 x ø10mm	4m	10 Bar	1710410-04
3/8" BSPT external thread	ø6,5 x ø10mm	6m	10 Bar	1710410-06
3/8" BSPT external thread	ø6,5 x ø10mm	8m	10 Bar	1710410-08
1/2" BSPT external thread	ø8 x ø12mm	4m	10 Bar	1710512-04
1/2" BSPT external thread	ø8 x ø12mm	6m	10 Bar	1710512-06
1/2" BSPT external thread	ø8 x ø12mm	8m	10 Bar	1710512-08
1/2" BSPT external thread	ø11x ø16mm	6m	10 Bar	1710716-06
1/2" BSPT external thread	ø11x ø16mm	8m	10 Bar	1710716-08



Flex Boy recoil hoses with Air Boy blowguns

Connection	Dim.	Work. length	Max. work. pressure	Code no.
1/4" BSPT external thread	ø5 x ø8mm & Air Boy Standard	2m	10 Bar	242802-000
1/4" BSPT external thread	ø5 x ø8mm & Air Boy Standard	4m	10 Bar	242804-000
1/4" BSPT external thread	ø5 x ø8mm & Air Boy Standard	6m	10 Bar	242806-000



Pneumatic hoses

Recoil hoses PUR - "Flex Boy"

Recoil hoses PUR - "Flex Boy"

Super flexible recoil hoses, capable of bending without being damaged. Maintains persistent flexibility at temperatures as low as -40°C. An oil-resistant hose whose superior qualities are acknowledged in all sectors of industry. We recommend that polyurethane hoses not be used in direct sunlight for long periods of time.

Technical data

Material: Polyurethane
 Working pressure: Max. 10 bar at +20°C
 Temperature range: -40°C to +60°C
 Surface hardness: Shore D52

Recoil hoses PUR - "Flex Boy" Series 530 coupling & Euro nipple

Connection	Dim.	Work. length	Max. work. pressure	Code no.
Series 530 coupling & nipple	ø5 x ø8mm	1m	10 Bar	1810208-01530
Series 530 coupling & nipple	ø5 x ø8mm	2m	10 Bar	1810208-02530
Series 530 coupling & nipple	ø5 x ø8mm	4m	10 Bar	1810208-04530
Series 530 coupling & nipple	ø5 x ø8mm	6m	10 Bar	1810208-06530
Series 530 coupling & nipple	ø5 x ø8mm	8m	10 Bar	1810208-08530
Series 530 coupling & nipple	ø6,5 x ø10mm	2m	10 Bar	1810410-02530
Series 530 coupling & nipple	ø6,5 x ø10mm	4m	10 Bar	1810410-04530
Series 530 coupling & nipple	ø6,5 x ø10mm	6m	10 Bar	1810410-06530
Series 530 coupling & nipple	ø6,5 x ø10mm	8m	10 Bar	1810410-08530
Series 530 coupling & nipple	ø8 x ø12mm	2m	10 Bar	1810512-02530
Series 530 coupling & nipple	ø8 x ø12mm	4m	10 Bar	1810512-04530
Series 530 coupling & nipple	ø8 x ø12mm	6m	10 Bar	1810512-06530
Series 530 coupling & nipple	ø8 x ø12mm	8m	10 Bar	1810512-08530



1810410-04530

Flex Boy recoil hoses with Air Boy blowguns, 530 coupling & Euro nipple

Connection	Dim.	Work. length	Max. work. pressure	Code no.
Series 530 coupling & nipple	ø5 x ø8mm & Air Boy Standard	2m	10 Bar	240802-000530
Series 530 coupling & nipple	ø5 x ø8mm & Air Boy Standard	4m	10 Bar	240804-000530
Series 530 coupling & nipple	ø5 x ø8mm & Air Boy Standard	6m	10 Bar	240806-000530