

## Galvanised compressed air receivers, operating pressure 11 bar

BOGE

Capacity litres	Dim. mm						ØG	Weight kg	Air- Inlet	Air outlet Ball	Inspections apertures
	A	ØB	C	D	E	F					
<b>Horizontal receivers</b>											
50	780	300	380	380	400	320	14	30	G ½	G ¾	2 x 1 sleeve on the back
90	995	350	390	500	550	330	14	37	G ¾	G ¾	
150	1360	400	410	480	800	350	14	66	G ½	G ½	1 hand hole
270	1540	500	570	625	800	500	19	100	G ½	G ½	
350	1610	550	620	660	900	550	19	125	G ¾	G ¾*	
500	1730	600	670	705	1100	600	24	150	G 1¼	G 1	
750	1828	750	730	856	1100	660	24	220	G 1¼	G 1	2 hand holes or 1 manhole (option)
1000	2070	800	790	885	1200	720	24	285	G 1¼	G 1¼	
2000	2170	1150	1200	1325	1300	1100	23	555	G 1½	G 2	1 manhole
3000	2675	1250	1350	1450	1500	1250	23	765	G 1½	G 2	
5000	3500	1400	1500	1600	2200	1400	23	1170	G 1½	G 2	1 manhole
10000	5370	1600	1600	1700	3700	1550	18	2100	DN 100	DN 100	

Capacity litres	A	ØB	C	F	ØG	height when installed		Weight kg	Air- Inlet	Air outlet Ball	Inspections apertures
						height when installed	height when installed				
<b>Vertical receivers</b>											
270	1765	500	500	460	13	1780		100	G 1	G ½	1 handhole
350	1835	550	550	510	13	1845		125	G 1	G ¾	
500	1980	600	655	525	22	2070		150	G 1½	G 1½	
750	2084	750	750	620	22	2130		220	G 1½	G 1½	
1000	2340	800	800	670	22	2400		285	G 1½	G 2	2 hand holes or 1 manhole (option)
2000	2390	1150	1000	1000	23	2510		555	G 2½	G 2½	
3000	2790	1250	1250	1150	23	2865		765	G 2½	G 2½	1 manhole
5000	3730	1400	1400	1300	23	3800		1170	G 2½	G 2½	
5000	3730	1400	1400	1300	23	3800		1180	DN 100	DN 100	
10000	5590	1600	1600	1340	-	5660		2100	DN 100	DN 100	

## Galvanised compressed air receivers, operating pressure 16 bar

BOGE

Capacity litres	Dim. mm						ØG	Weight kg	Air- Inlet	Air outlet Ball	Inspections apertures
	A	ØB	C	D	E	F					
<b>Horizontal receivers</b>											
50	780	300	380	380	400	320	14	37	G ½	G ¾	2 x 1 sleeve on the back
150	1310	400	410	480	800	350	14	74	G ½	G ½	
250	1380	500	570	625	800	500	19	113	G ¾	G ½	1 hand hole
350	1600	550	620	660	900	550	19	145	G ¾	G ¾	
500	1780	600	670	705	1100	600	24	180	G 1¼	G 1	
750	1860	750	730	856	1100	660	24	275	G 1¼	G 1	
1000	2100	800	790	885	1200	720	24	355	G 1¼	G 1¼	2 hand holes or 1 manhole (option)
2000	2170	1150	1200	1325	1300	1100	23	720	G 1½	G 2	
3000	2675	1250	1350	1450	1500	1250	23	935	G 1½	G 2	1 manhole
5000	3270	1400	1500	1600	2200	1400	23	1340	G 1½	G 2	
10000	5370	1600	1600	1700	3700	1550	18	2940	DN 100	DN 100	

Capacity litres	A	ØB	C	F	ØG	height when installed		Weight kg	Air- Inlet	Air outlet Ball	Inspections apertures
						height when installed	height when installed				
<b>Vertical receivers</b>											
250	1605	500	500	380	13	1615		113	G 1	G ½	1 hand hole
350	1835	550	550	510	13	1845		145	G 1	G ¾	
500	1995	600	600	525	22	2100		180	G 1½	G 1½	
750	2110	750	750	620	22	2155		275	G 1½	G 1½	
1000	2340	800	800	670	22	2400		355	G 1½	G 2	2 hand holes or 1 manhole (option)
2000	2410	1150	1150	1000	23	2510		720	G 2½	G 2½	
3000	2790	1250	1250	1150	23	2865		935	G 2½	G 2½	1 manhole
5000	3730	1400	1400	1300	23	3800		1340	G 2½	G 2½	
5000	3730	1400	1400	1300	23	3800		1350	DN 100	DN 100	
10000	5590	1600	1600	1340	-	5660		2940	DN 100	DN 100	

Compressed air receivers with higher operating pressures are available upon request